

SIHL Printer Settings



SIHL FACESTOCK 8002 PICOFILM WO-80 matt ZM1 and 8003 PICOFILM WO-110 matt ZM1 for EPSON Colour Label Printers

Printer	BEST SETTING	Additional settings
EPSON CW-C4000 with MK or BK black ink	Media Type: Synthetic Paper Print Quality: Quality	Print Quality mode: „Max. Speed“ - acceptable (draft level) „Speed“ - not recommended (high ink saturation) „Normal“ - good (lower resolution)
EPSON CW-C6500 with MK or BK black ink	Media Type: Synthetic Print Quality: Quality	Print Quality mode: „Max. Speed“ - acceptable (draft level) „Speed“ - not recommended (high ink saturation) „Normal“ - good (lower resolution)
EPSON TM-C7500 with MK black ink	Media Coating Type: Synthetic Printing speed: 150 or 300 mm/sec. Media Type: Automatic	Media Coating Type: „Plain“ - acceptable (draft level) „Matte 1“ - acceptable (draft level) „Matte 2“ - not recommended (high ink saturation)
EPSON TM-C7500G with BK black ink	Media Coating Type: Synthetic Printing speed: 150 or 300 mm/sec. Media Type: Automatic	Media Coating Type: „Plain“ - acceptable (draft level) „Matte 1“ - acceptable (draft level) „Matte 2“ - not recommended (high ink saturation)